



Product Specification

Last updated Sep-08

Page 1 of 1

DM791

Product	Double Coated Tape Clear
Liner	Red MOPP Film 0.08mm
Carrier	Transparent Mylar with thickness of 0.025mm
Adhesive	Cross linked solvent acrylic, pressure sensitive
Description	This tape has a strong Mylar base with a solvent acrylic adhesive giving it good adhesion and excellent long term holding power under broad temperature range. Resistant to weather conditions, UV, plasticizers and ageing. Good clarity, strong PP liner.
Range of application	Suitable for numerous industrial fixing applications, sign and display, light box poster, magnetic rubber
Application temperature	18°C - 25°C; R.H. 55%±10%

Total Thickness	0.095mm - 0.105mm		
Coating Thickness (Side A/B)	0.035mm--0.040mm		
Temperature resistance	-20°C - 180°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 5 cm		
Holding Power (Side A/B) (PSTC-7)	> 72 hrs 1 kg/2.5cmx2.5cm		
Holding Power for temperature resistance 80°C (PSTC-7)	> 5 hrs 0.5kg/25mmx25mm		
Adhesion (Side A/B) (PSTC-1)	g/25mm	OZ/0.6in	N/25mm
	>1500	>52.9	>14.64
Solvent resistance	Good		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.

Copyright © 2008 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu off all warrantees, expressed or implied, including the implied warrantees of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.
