



Product Specification

Last updated Feb-08

Page 1 of 1

DM189

Product	Double-Coated Tape
Liner	White PE paper 110gsm.
Carrier	Transparent Mylar with thickness of 0.025mm
Adhesive	Cross linked solvent acrylic, pressure sensitive
Description	This tape has a strong Mylar base with a high tack solvent acrylic adhesive giving it excellent holding power and adhesion. Good resistance to weather conditions, UV, plasticizers and ageing.
Range of application	Suitable for numerous fixing applications such as decorative and furniture trims, sign assembly, badge mounting, DIY and crafts.
Application temperature	18°C - 25°C; R.H. 55%±10%

Total Thickness	0.215mm - 0.225mm		
Coating Thickness (Side A/B)	0.095mm--0.100mm		
Temperature resistance	-20°C - 120°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 5 cm		
Holding Power (Side A/B) (PSTC-7)	> 24 hrs 1 kg/2.5cmx2.5cm		
Holding Power for temperature resistance 60°C (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm		
Adhesion (Side A/B) (PSTC-1)	g/15mm >2500	OZ/0.6in >88.19	N/15mm >24.4
Solvent resistance	Good		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.

Copyright © 2008 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu off all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.