

<b>Product</b>	Double coated PE foam
<b>Liner</b>	Yellow PE paper 90gsm
<b>Carrier</b>	Closed cell PE foam white, 67kg/m <sup>3</sup>
<b>Adhesive</b>	Solvent rubber resin, pressure sensitive
<b>Description</b>	This pressure sensitive mounting tape with rubber resin adhesive is suitable for interior applications and combines good initial tack with high shear performance. Suitable for use on moderately uneven surfaces. Not resistant to UV or plasticizers.
<b>Typical applications</b>	Kitchen hooks and towel hooks, mirror mounting, point-of-sale, other interior mounting applications where high shear is required.
<b>Application temperature</b>	18°C - 25°C

<b>Total Thickness</b>	1.0mm - 1.1mm		
<b>Coating Thickness (Side A/B)</b>	0.060mm - 0.065mm		
<b>Temperature resistance</b>	-10°C - 90°C		
<b>Initial Tack (Side A/B)</b> <b>(PSTC-6 #14 ball)</b>	< 2 cm		
<b>Holding Power (Side A/B)</b> <b>(PSTC-7)</b>	> 72 hrs 1 kg/2.5cmx2.5cm		
<b>Holding Power for temperature</b> <b>resistance 60°C (PSTC-7)</b>	N.A. 0.5kg/2.5cmx2.5cm		
<b>Adhesion (Side A/B)</b> <b>(PSTC-1)</b>	g/2.5cm >2000	OZ/in >70.55	N/2.5cm >19.50
<b>Solvent resistance</b>	Low		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure maximum adhesive contact.