



# Product Specification

Last updated February 08  
Page 1 of 1

## R2F-114 (1.0mm)

<b>Product</b>	Double coated PE foam
<b>Liner</b>	Yellow PE paper 90gsm
<b>Carrier</b>	Closed cell PE foam white
<b>Adhesive</b>	Solvent rubber resin, pressure sensitive
<b>Description</b>	This pressure sensitive mounting tape with rubber resin adhesive is suitable for interior applications and combines good initial tack with high shear. Suitable for use on moderately uneven surfaces. Not resistant to UV or plasticizers.
<b>Typical applications</b>	Kitchen hooks and towel hooks, mirror mounting, other interior mounting applications where high shear is required.
<b>Application temperature</b>	18°C - 25°C

<b>Total Thickness</b>	1.0mm - 1.1mm		
<b>Coating Thickness (Side A/B)</b>	0.060mm - 0.065mm		
<b>Temperature resistance</b>	-10°C - 90°C		
<b>Initial Tack (Side A/B) (PSTC-6 #14 ball)</b>	< 2 cm		
<b>Holding Power (Side A/B) (PSTC-7)</b>	> 72 hrs 1 kg/2.5cmx2.5cm		
<b>Holding Power for temperature resistance 60°C (PSTC-7)</b>	N.A. 0.5kg/2.5cmx2.5cm		
<b>Adhesion (Side A/B) (PSTC-1)</b>	g/2.5cm	OZ/in	N/2.5cm
	>2000	>70.55	>19.50
<b>Solvent resistance</b>	Low		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure maximum adhesive contact.

Copyright © 2008 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu off all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.