



Phone +44 (0)1543 509 539  
 Fax +44 (0)870 836 2125  
 sales@skdtapes.com  
 www.skdtapes.com

PO Box 4945  
 Cannock, Staffordshire  
 WS12 9DF  
 United Kingdom

## Security labels

In order to offer you the right solution in any situation we have introduced three unique types of tamper evident label material. Each designed to unmistakably reveal evidence of any attempt of fraud or theft with your valuable goods. Please allow us to explain...



**SK81xx**  
 This product will only leave the text itself behind on the surface on which the product was applied. The residue is permanent and difficult to remove. The message is visible on the item's surface as well as in the label.

**SK84xx / SK85xx**  
 This product will leave the full message behind on the surface on which the product was applied. The residue is permanent and difficult to remove. The message will be visible both on the surface as well as in the label.



**SK88xx**  
 This product leaves no residue on the item and will only show its void message in the label itself. It is suitable for items or packaging which are meant to be re-used.

Each product is available in a range of colours in any shape or format, rolls or labels. Custom designs for recommended additional security can include a unique surface print in one or more colours, custom void message, bar-coding, sequential numbering of individual pieces and UV-tracers.

**The 'x' in the code represents the colour. Standard colours are:**

0=Black, 1=Light Blue, 2=Red, 3=Green, 4=Yellow, 5=Silver, 6=Purple, 7=Transparent, 8=White, 9=Dark red, 10=Orange

For more information, samples or prices, please phone us now on +44 (0)1543 509 539, or email: [enquiries@skdtapes.com](mailto:enquiries@skdtapes.com)



	SK81	SK84	SK85	SK88
<b>Type</b>	Partial transfer	Total transfer Easy release	Total transfer	None transfer
<b>Liner</b>	Glassine paper	Glassine paper	Glassine paper	Glassine paper
<b>Backing</b>	Matte polyester	Matte polyester	Matte polyester	Matte polyester
<b>Adhesive</b>	Acrylic resin	Acrylic resin	Acrylic resin	Acrylic resin
<b>Total thickness</b>	0.07mm	0.11mm	0.11mm	0.11mm
<b>Temperature resistance</b>	-18°C - 80°C	-18°C - 80°C	-18°C - 80°C	-18°C - 80°C

**Tel +44 (0)1543 509 539 Fax +44 (0)870 836 2125**  
**sales@skdtapes.com www.skdtapes.com**